


# Designing scalable architectures for neural data acquisition

Adam Marblestone  
Church Lab  
Harvard Biophysics


PhD Thesis Defense  
April 2014

neuro

info



?




ISSUE DATE  
1 - 11/12/86  
2 - 15/12/86  
3 - 26/1/87



neuro

info



$$y_t(i) = P(-e_t | c_i(t)) \propto \prod_{j=1}^M \lambda_t^{m_j}(r_i^{m_j}) \quad (2)$$

where coincidence pattern  $c_i$  is the co-occurrence of  $r_i^{m_1}$ 'th Markov chain from child 1,  $r_i^{m_2}$ 'th Markov chain from child 2,  $\dots$ , and  $r_i^{m_M}$ 'th Markov chain from child  $M$ .

$$\lambda_t(g_r) = P(-e_0^t | g_r(t)) \propto \sum_{c_i(t) \in C^k} \alpha_t(c_i, g_r) \quad (3)$$

$$\alpha_t(c_i, g_r) = P(-e_t | c_i(t)) \sum_{c_j(t-1) \in C^k} P(c_i(t) | c_j(t-1), g_r) \alpha_{t-1}(c_j, g_r) \quad (4)$$

$$\alpha_0(c_i, g_r) = P(-e_0 | c_i(t=0)) P(c_i(t=0) | g_r) \quad (5)$$

$$Bel_t(c_i) \propto \sum_{g_r \in G^k} \beta_t(c_i, g_r) \quad (6)$$

$$\beta_t(c_i, g_r) = P(-e_t | c_i(t)) \sum_{c_j(t-1) \in C^k} P(c_i(t) | c_j(t-1), g_r) \beta_{t-1}(c_j, g_r) \quad (7)$$

$$\beta_0(c_i, g_r) = P(-e_0 | c_i(t=0)) P(c_i | g_r) \pi_0(g_r) \quad (8)$$


$$\pi^{m_i}(g_r) \propto \sum_i I(c_i) Bel(c_i) \quad (9)$$

where

$$I(c_i) = \begin{cases} 1, & \text{if } g_r^{m_i} \text{ is a component of } c_i \\ 0, & \text{otherwise} \end{cases} \quad (10)$$




# Coarse-grained brain *maps* give un-testable *models*






# Coarse-grained brain *maps* give un-testable *models*



thalamic gating of “copy and paste” operations between cortical working memory buffers, executing a sequence of steps controlled by the basal ganglia




# Coarse-grained brain *maps* give un-testable *models*



thalamic gating of “copy and paste” operations between cortical working memory buffers, executing a sequence of steps controlled by the basal ganglia


# The dream of a *single* “canonical” cortical circuit

Likely a gross over-simplification of reality





# Molecularly-defined cortical connectivity



(retrograde labeling + FISH)


# Emerging picture: *many* computations, not one

| Computation                                    | Algorithmic/<br>representational<br>realization                                                            | Neural<br>implementation(s)                                                                                                                                                                         | Brain<br>location(s)                                         |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| Rapid perceptual classification                | Receptive fields, pooling and local contrast normalization <sup>58,61</sup>                                | Hierarchies of simple and complex cells <sup>62</sup>                                                                                                                                               | Visual system                                                |
| Complex spatiotemporal pattern recognition     | Bayesian belief propagation <sup>19,63</sup>                                                               | Feedforward and feedback pathways in cortical hierarchy <sup>19</sup>                                                                                                                               | Sensory hierarchies                                          |
| Learning efficient coding of inputs            | Sparse coding <sup>64</sup>                                                                                | Thresholding and local competition <sup>65</sup>                                                                                                                                                    | Sensory and other systems                                    |
| Working memory                                 | Continuous or discrete attractor states in networks <sup>66,67</sup>                                       | Persistent activity in recurrent networks <sup>68</sup>                                                                                                                                             | Prefrontal cortex                                            |
| Decision making                                | Temporal-difference reinforcement learning algorithms <sup>69,70</sup> ; actor-critic models <sup>71</sup> | Cortically implemented Bayesian inference networks combined with temporal difference reinforcement learning via the dopamine system and action selection systems in the basal ganglia <sup>72</sup> | Prefrontal cortex                                            |
|                                                | Winner-take-all networks <sup>73</sup>                                                                     | Recurrent networks coupled via lateral inhibition <sup>73</sup>                                                                                                                                     | Prefrontal cortex                                            |
| Gating of information flow                     | Context-dependent tuning of activity in recurrent network dynamics <sup>74</sup>                           | Recurrent neural networks implementing line attractors and selection vectors <sup>74</sup>                                                                                                          | Prefrontal cortex                                            |
|                                                | Shifter circuits <sup>64,75</sup>                                                                          | Divergent excitatory relays and input-selective shunting inhibition in dendrites <sup>76</sup>                                                                                                      | Visual system                                                |
| Gain control                                   | Divisive normalization <sup>35</sup>                                                                       | Shunting inhibition in networks or balanced background synaptic excitation and inhibition <sup>77</sup>                                                                                             | Common across many cortical areas                            |
| Sequencing of events over time <sup>78</sup>   | Feed-forward cascades; Serial working memories <sup>79</sup>                                               | Synfire chains <sup>80-82</sup> ; Thalamo-cortico-striatal loops <sup>83,84</sup>                                                                                                                   | Common across many cortical areas                            |
| Representation and transformation of variables | Population coding <sup>85</sup>                                                                            | Time-varying firing rates of cosine-tuned neurons representing dot products with encoding vectors                                                                                                   | Motor cortex                                                 |
| Variable binding                               | Holographic reduced representations <sup>56,86</sup>                                                       | Circular convolution of vectors represented by neural population codes                                                                                                                              | Cortical areas involved in sequential or symbolic processing |
|                                                | Dynamic binding <sup>87,88</sup>                                                                           | Neural synchronization <sup>89</sup>                                                                                                                                                                |                                                              |



# Multi-level complexity

*Example: hundreds of proteins in each synaptic vesicle*



Nature Reviews | **Neuroscience**

Deep molecular diversity of  
mammalian synapses: why it matters  
and how to measure it

Nancy A. O'Rourke, Nicholas C. Weiler, Kristina D. Micheva and Stephen J. Smith

# Multi-level complexity

*Example: the physical basis of long-term memory is still uncertain*

**Very long-term memories may be stored in the pattern of holes in the perineuronal net** (i.e., in the extracellular matrix)

**Roger Y. Tsien<sup>1</sup>**

Department of Pharmacology, Department of Chemistry and Biochemistry, and Howard Hughes Medical Institute, University of California at San Diego, La Jolla, CA 92093-0647

Contributed by Roger Y. Tsien, June 3, 2013 (sent for review May 16, 2013)

(vs. bistable auto-phosphorylating kinases at the synapse)



# How to cope with the brain's complexity?

**A**ctivity history

**B**ehavior

**C**onnectivity (circuit diagram)

**D**evelopment (cell lineage tree)

**E**xpression (epigenetic cell types,  
+ single-synapse proteomes)

**Need:** a technology to cheaply / rapidly  
measure all these variables in a single brain.

**Need:** (sub)cellular resolution + whole brain scope.




# How to cope with the brain's complexity?

## Rosetta Brains:

A, B, C, D & E  
comprehensively  
on a single brain

allows correlations  
across variables/levels





**Q for thesis:**

What would such a technology **conceivably** look like?

# Activity history

**B**ehavior


**C**onnectivity (circuit diagram)

**D**evelopment (cell lineage tree)

**E**xpression (epigenetic cell types,  
+ single-synapse proteomes)


We want a technology which can cheaply / easily  
measure all these variables in a single brain.

Need (sub)cellular resolution + whole brain scope.





# “every spike from every neuron” in a mammalian brain



## Mouse brain:

100M neurons  
>100B connections  
1-1000 Hz firing rates  
0.5 cc volume



**nobody has written down a design that clearly**  
**solves the problem**  
**does not violate any laws of physics**  
**does not severely damage the brain**




# Physics constraints on brain activity mapping

< 2C temperature change:


→ < 50 mW steady-state power dissipation

< 1% tissue volume displacement


A) Electrical




B) Optical




C) Magnetic Resonance




D) Molecular




# Physics constraints on brain activity mapping



100-200  $\mu\text{m}$  max recording radius



# Physics constraints on brain activity mapping



**$r_{\text{max}} \sim 130 \mu\text{m}$**

**signal size  $\sim 100\text{-}1000 \mu\text{V}$**

**noise floor  $\sim 10\text{-}20 \mu\text{V}$**

**SNR  $< 100$**

$$V_{\text{johnson}} = [4k_b T R(BW)]^{1/2} \sim 9 \mu\text{V}$$


amplifier noise  $\sim 1 \mu\text{V}$

noise from other neurons




# Physics constraints on brain activity mapping

**750k -7.5M electrodes for 75M mouse neurons**



current spike sorting algorithms:  $< 10$  neurons / electrode  
information theory estimate:  $< 100$  neurons / electrode  
estimate from max recording radius:  $< 1000$  neurons / electrode

# Physics constraints on brain activity mapping



**wirelessly-powered RFID chip**


$> 10 \text{ pJ}$  per transmitted bit

$\times 100 \text{ Gbit/sec} = \mathbf{1W}$

need at **2-3 orders of magnitude** improvement  
in power efficiency of electronics  
to use embedded chips for whole-brain recording

# Physics constraints on brain activity mapping

## power limits on switching elements




[CMOS data from Rod Tucker]

Marblestone et al, Front. Comp. Neurosci (2013): **with >17 co-authors**



# Physics constraints on brain activity mapping


## power limits on data transmission



### Workarounds:

store data locally and read out slowly


use ultrasound or infrared/visible light rather than RF / microwave transmission




# Back to the drawing board



# What if each cell could record its own activity?



=  
0101001010101010010101  
0101010101001010110111  
0010110101010111010011  
=






got \$9M NIH grant to pursue this




# a molecular recording device in each neuron

Encode information via control of polymerase **error rate**





vs.



electronic

**Bandwidth:** (1 bit / 1 ms / neuron) x (1e8 neurons) = **100 gigabit / s**  
to read out a mouse brain at 1 bit per ms per neuron in real time

**readout of information stored in biomolecules can be arbitrarily slow**


**Power:** CMOS bit switching at 1000 Hz consumes more energy than a neuron

**molecular recorders are 5-6 orders of magnitude more efficient**


|                                         |                                                                              |                  |
|-----------------------------------------|------------------------------------------------------------------------------|------------------|
| <u>ultimate</u> limit:                  | $kT \times \log(2) \text{ per bit} \times 1000 \text{ bps}$                  | <b>3e-18 W</b>   |
| <u>practical</u> limit for electronics: | $40 \text{ kT per bit} \times 1000 \text{ bps}$                              | <b>1e-16 W</b>   |
| <u>current</u> CMOS:                    | 1e6 worse than the 40 kT per bit limit                                       | <b>1e-10 W</b>   |
|                                         | $1 \text{ fF} \times (1 \text{ V})^2 \times 1000 \text{ Hz}$                 | <b>1e-12 W</b>   |
| 1 <u>neuron</u> :                       | $(1 \text{ e8 ATP / spike}) \times 100 \text{ Hz}$                           | <b>5e-10 W</b>   |
|                                         | $(25 \text{ W / human brain}) \times (1 \text{ human brain / 1e11 neurons})$ | <b>2.5e-10 W</b> |
| <u>ATP</u> consumption at 2000 Hz:      | $2000 \text{ Hz} \times (5 \text{ e-20 J / ATP})$                            | <b>1e-16 W</b>   |



vs.




electronic






# Sequencing-based screening for ion-dependent DNA pol error rates




biochemistry via sequencing

# Sequencing-based screening for ion-dependent DNA pol error rates



biochemistry via sequencing

# Sequencing-based screening for ion-dependent DNA pol error rates





# Iota pol: gets “A” wrong 70% of the time

Example of a good read aligned with revcomp(template):


forward primer  
binding site

TTTTTGATGGTCATAGCTGTTGTATTTTTGTTTTCAATTCATTCGTTTGTTGCTTCCTTCGCTGTGCTGCTGGCATGCTGATTGGCTTGTTTGATTT



deletion

GATGGTCATAGCTGTTGTATTTTTATTTCATTCATTCATTCATTGCATCCATCGACTGAGCTACTGACGTACTGACTTACTGACTTATGATTT

↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑




# DNA pol offerings from Nature



needs custom  
pol engineering

# Encoding time-series into DNA



computer

+Mn

solenoid valve


+Mg

solenoid valve

flow cell with primer immobilized


waste

circular template







# Theoretical temporal resolution of a DNAP ensemble



$$p(\Delta t)_{2\text{-paths}} = P \frac{e^{-\Delta t/\tau_p}}{\tau_p} + (1-P) \frac{e^{-\Delta t/\tau_c}}{\tau_c}$$



even with no “paused state”,  
dwell times are stochastic



nucleotide  $\longleftrightarrow$  time  
mapping smears over time

# Theoretical temporal resolution of a DNAP ensemble

## In the absence of a synchronization / clock mechanism:

**< 10 ms** temporal resolution does not persist for  $>$  seconds, even with  $> 1000$  simultaneously-replicated templates per cell

unless a faster-than-natural polymerase can be engineered  
(while maintaining other favorable properties)


**~ 100 ms** temporal resolution is feasible w/ optimal combination of individual naturally-occurring polymerase parameters

**~ 1000 ms** temporal resolution feasible with realistic near-term polymerase parameters

**need ensemble synchronization to reach single-spike resolution**

# slow-timescale *gene expression* tickertape

Hack CRISPR  
bacterial immune system  
for molecular recording




**Activity history**  
**Behavior**

**Connectivity** (circuit diagram)

**Development** (cell lineage tree)

**Expression** (epigenetic cell types,  
+ single-synapse proteomes)




**Need:** a technology to cheaply / rapidly  
measure all these variables in a single brain.

**Need:** (sub)cellular resolution + whole brain scope.




long-range connections




[Gong et al, 2013]


dense 3D circuitry:  
>1 synapse (connection) per  $\mu\text{m}^3$



[Mischenko, 2010]



*Assumption:* widely believed that electron microscopy (EM) is the only viable method for cellular-resolution connectomics



302 neurons: 50 person-years for C. elegans

analysis



**\$1B** for mouse w/ **no molecular info**



Can't run a simulation






# BrainBow: random color for each neuron

... *analog* implementation of a profound *digital* idea

**Problem:** only ~20 distinguishable colors in practice...

**a** XFP combinations

| Outcome for each copy |   |   | Resulting colour |
|-----------------------|---|---|------------------|
| 1                     | 2 | 3 |                  |
| C                     | C | C | Blue             |
| C                     | C | Y | Light blue       |
| C                     | Y | Y | Blue-green       |
| Y                     | Y | Y | Green            |
| Y                     | Y | R | Light green      |
| Y                     | R | R | Orange           |
| R                     | R | R | Red              |
| R                     | R | C | Magenta          |
| R                     | C | C | Purple           |
| R                     | C | Y | Grey             |



Lichtman, Sanes, Livet et al




$4^N$  possible DNA sequences of length N “letters”



=  
**01010010101010010101  
0101010101001010110111  
0010110101010111010011**  
=





## Strategy #1: deliver random DNA strings by cloning into a virus

Duplicate barcode probability per mouse brain: negligible for 30 nt barcodes

$$P(j, n) = n! * \text{Binomial}(4^j, n) / (4^j)^n$$

where  $n$  is the size of the cell population and  $j$  is the DNA barcode length in nucleotides.  $P(j, n)$  can be approximated by


$$P(j, n) \approx \exp\left(-\frac{n^2/2}{4^j}\right)$$

such that for  $n = 7.5 \times 10^7$  neurons and  $j = 31$  base-long barcodes, the probability of a duplication  $1 - P(j, n) < 0.001$ . This corresponds to a total barcode population size of  $4^{31} \approx 5 \times 10^{18}$ .

## Strategy #2: have each cell *make* its own barcode in-vivo

Example: invertase


Theoretical diversity



$$k! \times 2^k$$

*Other in-vivo barcoding strategies are also under way in the Church lab*

# Zador: Pair barcodes of connected cells, then sequence



**extracts connectivity**



**but**

**1) scrambles cell positions**

**2) hard to integrate w/  
molecular “annotations”  
(e.g., gene expression)**

# digital 4<sup>N</sup>color microscopy

## Fluorescent In-Situ DNA Sequencing (FISSEQ):




## Highly Multiplexed Subcellular RNA Sequencing in Situ



Je Hyuk Lee,<sup>1,2\*†</sup> Evan R. Daugharthy,<sup>1,2,4\*</sup> Jonathan Scheiman,<sup>1,2</sup> Reza Kalhor,<sup>2</sup> Joyce L. Yang,<sup>2</sup> Thomas C. Ferrante,<sup>1</sup> Richard Terry,<sup>1</sup> Sauveur S. F. Jeanty,<sup>1</sup> Chao Li,<sup>1</sup> Ryoji Amamoto,<sup>3</sup> Derek T. Peters,<sup>3</sup> Brian M. Turczyk,<sup>1</sup> Adam H. Marblestone,<sup>1,2</sup> Samuel A. Inverso,<sup>1</sup> Amy Bernard,<sup>5</sup> Prashant Mali,<sup>2</sup> Xavier Rios,<sup>2</sup> John Aach,<sup>2</sup> George M. Church<sup>1,2†</sup>



# digital 4<sup>N</sup> color microscopy




## Fluorescent In-Situ DNA Sequencing (FISSEQ):




## Highly Multiplexed Subcellular RNA Sequencing in Situ

Je Hyuk Lee,<sup>1,2\*†</sup> Evan R. Daugharthy,<sup>1,2,4\*</sup> Jonathan Scheiman,<sup>1,2</sup> Reza Kalhor,<sup>2</sup> Joyce L. Yang,<sup>2</sup> Thomas C. Ferrante,<sup>1</sup> Richard Terry,<sup>1</sup> Sauveur S. F. Jeanty,<sup>1</sup> Chao Li,<sup>1</sup> Ryoji Amamoto,<sup>3</sup> Derek T. Peters,<sup>3</sup> Brian M. Turczyk,<sup>1</sup> Adam H. Marblestone,<sup>1,2</sup> Samuel A. Inverso,<sup>1</sup> Amy Bernard,<sup>5</sup> Prashant Mali,<sup>2</sup> Xavier Rios,<sup>2</sup> John Aach,<sup>2</sup> George M. Church<sup>1,2†</sup>


# digital 4<sup>N</sup> color microscopy



# digital 4<sup>N</sup> color microscopy



# digital 4<sup>N</sup> color microscopy




**A much easier problem than whole-brain electron microscopy!**



# digital 4<sup>N</sup>color microscopy


## Example: “array tomography” thin sectioning + fluorescence microscopy



## Array Tomography: A New Tool for Imaging the Molecular Architecture and Ultrastructure of Neural Circuits




**Red dots are synapses, resolved w/ diff. limited optics via thin-sectioning**



**Smith lab, Stanford**



# digital 4<sup>N</sup>color microscopy



Enhance effective resolution by “stratifying” molecules into different image frames:

$S^{(1/3)}$  xyz improvement where S is slowdown factor


Use prior information about entire pool of barcodes to de-mix multiple signals from a single resolution voxel:

35-base barcodes suffice for no deconvolution ambiguities in mouse



# digital $4^N$ color microscopy


$$P(\text{ambiguity}) < \frac{n^2 \cdot 2^N}{4^{2N}} = n^2 \cdot 2^{-3N}$$

*Simulations of informatic deconvolution verify estimated scaling behavior*










# The Rosetta Brain integration project

**Activity**  
**Behavior**  
**Connectivity**  
**Development**  
**Expression**



Molecular recordings





In-vivo-generated  
cell barcodes  
(update 1x per division)



Transcripts




DNA-barcoded antibodies



**FISSEQ**  
(Lee et al 2014)





# Well-known “systems engineering” methods by-&-for the sciences of *simplicity*...





# How to extend to the sciences of *complexity*?





# Further reading

frontiers in  
**COMPUTATIONAL NEUROSCIENCE**

**HYPOTHESIS AND THEORY ARTICLE**

published: 21 October 2013  
doi: 10.3389/fncom.2013.00137



## Physical principles for scalable neural recording

**Adam H. Marblestone<sup>1,2\*</sup>, Bradley M. Zamft<sup>3†</sup>, Yael G. Maguire<sup>3,4</sup>, Mikhail G. Shapiro<sup>5</sup>, Thaddeus R. Cybulski<sup>6</sup>, Joshua I. Glaser<sup>6</sup>, Dario Amodei<sup>7</sup>, P. Benjamin Stranges<sup>3</sup>, Reza Kalhor<sup>3</sup>, David A. Dalrymple<sup>1,8,9</sup>, Dongjin Seo<sup>10</sup>, Elad Alon<sup>10</sup>, Michel M. Maharbiz<sup>10</sup>, Jose M. Carmena<sup>10,11</sup>, Jan M. Rabaey<sup>10</sup>, Edward S. Boyden<sup>9,12‡</sup>, George M. Church<sup>1,2,3‡</sup> and Konrad P. Kording<sup>13,14‡</sup>**

## Rosetta Brains: A Strategy for Molecularly-Annotated Connectomics

Adam H Marblestone, Evan R Daugharthy, Reza Kalhor, Ian D Peikon, Justus M Kebschull, Seth L Shipman, Yuriy Mishchenko, Je Hyuk Lee, Konrad P Kording, Edward S Boyden, Anthony M Zador, George M Church

OPEN ACCESS Freely available online




## Measuring Cation Dependent DNA Polymerase Fidelity Landscapes by Deep Sequencing

**Bradley Michael Zamft<sup>1‡</sup>, Adam H. Marblestone<sup>2,9‡</sup>, Konrad Kording<sup>3,8</sup>, Daniel Schmidt<sup>4,5,7</sup>, Daniel Martin-Alarcon<sup>4,5,7</sup>, Keith Tyo<sup>6</sup>, Edward S. Boyden<sup>4,5,7</sup>, George Church<sup>1,2\*</sup>**

## Highly Multiplexed Subcellular RNA Sequencing in Situ

Je Hyuk Lee,<sup>1,2\*†</sup> Evan R. Daugharthy,<sup>1,2,4\*</sup> Jonathan Scheiman,<sup>1,2</sup> Reza Kalhor,<sup>2</sup> Joyce L. Yang,<sup>2</sup> Thomas C. Ferrante,<sup>1</sup> Richard Terry,<sup>1</sup> Sauveur S. F. Jeanty,<sup>1</sup> Chao Li,<sup>1</sup> Ryoji Amamoto,<sup>3</sup> Derek T. Peters,<sup>3</sup> Brian M. Turczyk,<sup>1</sup> Adam H. Marblestone,<sup>1,2</sup> Samuel A. Inverso,<sup>1</sup> Amy Bernard,<sup>5</sup> Prashant Mali,<sup>2</sup> Xavier Rios,<sup>2</sup> John Aach,<sup>2</sup> George M. Church<sup>1,2†</sup>



OPEN ACCESS Freely available online



## Statistical Analysis of Molecular Signal Recording

**Joshua I. Glaser<sup>1\*</sup>, Bradley M. Zamft<sup>2‡</sup>, Adam H. Marblestone<sup>3,4‡</sup>, Jeffrey R. Moffitt<sup>5</sup>, Keith Tyo<sup>6</sup>, Edward S. Boyden<sup>7,8,9</sup>, George Church<sup>2,3,4</sup>, Konrad P. Kording<sup>1,10,11</sup>**

## Conneconomics: The Economics of Dense, Large-Scale, High-Resolution Neural Connectomics

Adam H Marblestone, Evan R Daugharthy, Reza Kalhor, Ian D Peikon, Justus M Kebschull, Seth L Shipman, Yuriy Mishchenko, Je Hyuk Lee, David A Dalrymple, Bradley M Zamft, Konrad P Kording, Edward S Boyden, Anthony M Zador, George M Church

doi: 10.1101/001214